IN THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

- 1. (Currently Amended) An arrangement in a mechanical shaft seal, comprising:
- a first sliding surface part rotating with a shaft in relation to a frame; and
- a second sliding surface part fastened to <u>at least one of</u> the frame and/or to <u>or</u> a separate frame part that is non-rotatable in relation thereto,

wherein:

- the first sliding surface part and the second sliding surface part are provided with sliding surfaces pressed against one another,
- a first additional part is arranged to connect the first sliding surface part to at least one of the shaft and/or and an a first insertion part fastened to the shaft and is configured to rotate rotating therewith in order to transfer the rotating motion from the shaft to the first sliding surface part, and
- a second additional part <u>is arranged</u> to connect the second sliding surface part to the frame or at least to one <u>second</u> insertion part connected to the frame in order to prevent the rotation of the second sliding surface part in relation to the frame, and
- at least one of the first additional part arranged to transfer the rotation torque of at least one of the shaft and/or and the second additional part receiving torque is a super elastic memory metal element arranged to bend within the limits of the reversible deformation of the material.
- (Currently Amended) The arrangement of An arrangement as elaimed in claim 1, wherein all the first and second additional parts are memory metal elements.
- (Currently Amended) <u>The arrangement of An arrangement as claimed claim 1</u>, wherein all the first and second additional parts are pins.
- (Currently Amended) <u>The arrangement of An arrangement as claimed claim 1</u>, wherein all the first and second additional parts are threaded pins.

Application No. 10/588,856 Attorney Docket No. 44655-356508

Page 4 of 7

 (Currently Amended) <u>The arrangement of An arrangement as claimed-claim 1</u>, wherein all the first and second additional parts are plates.

- (Currently Amended) <u>The arrangement of An arrangement as claimed</u> claim 1, wherein all the first and second additional parts are rings.
- 7. (Currently Amended) <u>The arrangement of An arrangement as claimed claim 1</u>, wherein the first and second additional parts are machining features of <u>at least one of</u> the first sliding surface part and/or-of and the second sliding surface part.
- 8. (Currently Amended) The arrangement of An arrangement as claimed claim 1, wherein the arrangement <u>further also</u> comprises at least one spring, which is arranged to press opposite sliding surfaces of the first sliding surface part and the second sliding surface part against one another.
- 9. (Currently Amended) The arrangement of An arrangement as claimed claim 8, wherein the arrangement comprises a the second insertion part is movably fastened in the longitudinal direction of the shaft to the frame, which is connected to the second sliding surface part which is pressed using the spring against the second sliding surface part, the sliding surface of the spring being further pressed against the sliding surface of the first sliding surface part.